

# PRODUCT INFORMATION



**TITE-SEAL®**  
**GASKET & JOINT SEALING COMPOUND**  
**MEDIUM WEIGHT**

**CODE: T25-**

**PAGE: 1 of 1**

**DATE: April, 97**

**FUNCTION AND APPLICATION:** Seals with gasket...or as a gasket. Seals pumps, tanks, pressed plates, covers, pans, etc., for pipe threads and imperfect or uneven surfaces. For general gasketing and machine joints, cylinder heads, manifolds, differentials, transmissions, muffler joints. For sealing radiator hose connections... as a filler for water pump packing. Used as a gasket for gear housing that must retain oil and grease on appliances of all types.

**OUTSTANDING PROPERTIES:** TITE-SEAL® GASKET & JOINT SEALING COMPOUND is heat-proof, vibration-proof, non-solvent, non-shrinking, non-crumbling, non-cracking. Prevents rust, corrosion and seizure of joints, bolts, nuts, studs and threaded fittings. It withstands high temperatures and pressures, the actions of water, gasoline, kerosene, grease, oil, L-P and natural gas, steam, hot or cold water, glycerin, ethylene glycol, ammonia, etc.

**USE DIRECTIONS:** TITE-SEAL® MEDIUM WEIGHT will form seals at a temperature range of 30 to 300°F. Before applying wipe surfaces dry and clean. Then simply spread on. With gaskets: coat joint surfaces, spreading evenly. Without gaskets: coat joint surfaces and embed small thread or string as a binder. As a filler: apply as a bond between regular packing and metal surfaces. Do not use a thinner.

**PRECAUTIONS:** Contains a mixture of vegetable oils. May be skin and eye irritant to sensitive persons. Harmful if swallowed. **FIRST AID:** In case of eye contact flush with water for at least 15 minutes. For skin contact, wash with soap and water. If ingested, drink 2 glasses of milk: do not induce vomiting. Call a physician immediately.

**STORAGE & HANDLING:** Store in a cool place below 120°F. away from acids, ignition sources and oxidizing agents. Keep lid tightly closed when not in use. Wearing contact lenses while working with this product is inadvisable. Keep away from children.

**DISPOSAL:** Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

**CONTAINER DESCRIPTION:** This product is available in 1 lb, 5 lbs, and 25 lbs cans sizes .

## **Radiator Specialty Company**

P.O. BOX 34689 / CHARLOTTE, N.C. 28234 / TELEPHONE 704-377-6555

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.